

ACRYBASE

Acrylic primer in water emulsion

CHARACTERISTICS

Acrybase is a styrene-acrylic based primer in water emulsion applied before the application of acrylic waterproofing on roofing or floor slabs and for resurfacing acrylic sports surfaces laid over old acrylic coverings. Suitably diluted with water, Acrybase has high penetrating, fixative and consolidating properties and is ideal for porous decks in cement, brick etc....

APPEARANCE

Milky white low-viscosity liquid, transparent after drying.

CHARACTERISTICS OF THE LIQUID PRODUCT

Characteristic	U.M.	Value	Tolerance
Specific weight	kg/dm ³	1,03	± 0,05
Dry mass residue	%	23	± 1
Efflux time at 23°C (with Ford cup, hole no. 3)	sec	26	± 2

LAYING INSTRUCTIONS

Toolings	Thinner	Type of thinner	Cleaning method
Brush	approx. 30 %	Water	Water
Roller	approx. 30 %	Water	Water
Spray	approx. 40 %	Water	Water

PREPARATION OF THE LAYING SURFACE

Ensure that the deck is clean and dry removing all traces of dirt, grease and loose parts, if necessary, repair excessive roughness and ensure sufficient slope to ensure rainwater runoff.

CONSUMPTION

Coverage depends on the absorbing properties of the deck. Coverage is generally approx. 200 ml/sq.m. on regular cement decks; 100 ml/sq.m. to resurface old acrylic sports flooring; approx. 300 ml/sq.m. as fixative for slate chips.

APPLICATION INSTRUCTIONS

Temperature limit during application: MIN 10°C - MAX 40°C.
Product must be perfectly dry before exposure to fog, rain or frost.

DRYING OR HARDENING AT 23°C AND R.H. OF 50%

On surface	20'
To touch	45'
Interval between coatings	4 h

PACKAGING

Colours available	Transparent (dry)
Packaging	16 lt

STORAGE INSTRUCTIONS

Storage temperature	MIN 3°C - MAX 40°C
Stability in the original package	12 months

SAFETY STANDARDS

Please read the safety data sheet carefully before using this product.

The information contained in this technical data sheet is based on our scientific knowledge and practical experience. The same therefore do not imply and warranty or responsibility by CASALI S.p.A. on the use of its products and do not exonerate the purchaser from carrying out practical tests to ensure that the product is suitable for use in the actual operating conditions. CASALI S.p.A. reserves the right to modify the characteristics of its products at any time without notice.