

ACRYBASE S

Solvent-based acrylic primer

CHARACTERISTICS

Acrybase S is a solvent-based primer for acrylic products or similar. Acrybase S is generally used on low or non absorbing decks such as stoneware, fibre cement, bituminous membranes, metal surfaces, etc... but may also be used on absorbing surfaces (concrete).

APPEARANCE

Transparent colourless low-viscosity liquid; typical odour of organic solvents.

CHARACTERISTICS OF THE LIQUID PRODUCT

Characteristic	U.M.	Value	Tolerance
Specific weight	kg/dm ³	0,91	± 0,02
Dry mass residue	%	18	± 1
Efflux time at 23°C (with Ford cup, hole no. 3)	sec	29	± 2

LAYING INSTRUCTIONS

Toolings	Thinner	Type of thinner	Cleaning method
Brush	Ready for use	-	DIL S1
Roller	Ready for use	-	DIL S1
Spray	Ready for use	-	DIL S1

PREPARATION OF THE LAYING SURFACE

Ensure that the deck is clean and dry removing all traces of dirt, grease and loose parts, if necessary, repair excessive roughness and ensure sufficient slope to ensure rainwater runoff.

CONSUMPTION

Coverage is generally approx. 100 ml/sq.m for non-porous decks, approx. 150 ml/sq.m. for low-porous decks and approx. 220 ml/sq.m. for cement decks.

APPLICATION INSTRUCTIONS

Environmental and deck temperature limit during application: MIN 10°C - MAX 40°C.
Product must be perfectly dry before exposure to fog, rain or frost.

DRYING OR HARDENING AT 23°C AND R.H. OF 50%

On surface	1 h
To touch	2 h
Interval between coatings	24 h

PACKAGING

Colours available	Transparent
Packaging	10 lt

STORAGE INSTRUCTIONS

Storage temperature	MIN 3°C - MAX 40°C
Stability in the original package	24 months

SAFETY STANDARDS

Please read the safety data sheet carefully before using this product.

The information contained in this technical data sheet is based on our scientific knowledge and practical experience. The same therefore do not imply and warranty or responsibility by CASALI S.p.A. on the use of its products and do not exonerate the purchaser from carrying out practical tests to ensure that the product is suitable for use in the actual operating conditions. CASALI S.p.A. reserves the right to modify the characteristics of its products at any time without notice.